

PRODUCT NAME: Carrara Fine Texture Tint Base  
 PRODUCT CODE: CAR-FMTB-05

HMIS CODES: H F R P  
 2\* 0 0 1

===== SECTION I - MANUFACTURER IDENTIFICATION =====

PRODUCER'S NAME: GLOBAL COATINGS, INC.  
 ADDRESS : P.O. BOX 340485  
 AUSTIN, TX 78734  
 INITIAL(FIRST CALL) (512) 267-5888  
 EMERGENCY PHONE : DATE PRINTED : 7/1/99  
 DATE REVISED : Oct. 2006  
 INFORMATION PHONE : (512) 267-5888 NAME OF PREPARER : ENVIRONMENTAL SECT.

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
# DOLOMITE CRYSTALLINE SILICA AS QUARTZ, <1%. CAS# 14808-60-7, ACGIH TLV-0.1MG/M3 TWA, OSHA PE-0.1MG/M3 TWA. MAGNESIUM CARBONATE, CAS#546-93-0, 40-50%, ACGIH TLV-10MG/M3 TWA, OSHA PEL-15MG/M3 TWA TOTAL DUST, 5MG/M3 TWA, RESPIRABLE FRACTION. CALCIUM CARBONATE, CAS#471-34-1, 50-60%, ACGIH TLV-10 MG/M3 TWA, OSHA PEL-15MG/M3 TWA TOTAL DUST, 5MG/M3 TWA RESPIRABLE FRACTION.	MIXTURE	N/A N/A	56.3
ACRYLIC POLYMER (CONTAINS AMMONIA, CAS #7664-41-7 AT 0.2% MAX.) THE FOLLOWING EXPOSURE GUIDELINES ARE FOR THE AMMONIA CONTAINED IN THIS RAW MATERIAL AT 0.2% MAX. MANUFACTURER OF THIS RAW MATERIAL SUGGESTS: TWA-25PM. STEL-35 PPM. ACGIH: TLV-25 PPM. STEL-35 PPM. OSHA: TWA-NONE ESTABLISHED. STEL-35PPM.	MIXTURE	17 68F/20C	13
CALCIUM CARBONATE OSHA PEL-15MG/M3, TOTAL DUST, 5MG/M3, RESPIRABLE DUST. ACGIH TLV-10 MG/M3, TOTAL DUST CONTAINING NO ASBESTOS AND <1% FREE SILICA. IF SILICA LEVELS ABOVE 1.0% ARE PRESENT, THE TLV VALUE IS 0.1 MG OF RESPIRABLE SILICA PER CU. METER FOR BOTH OSHA PEL AND ACGIH TLV.	471-34-1	N/A N/A	10
# DOLOMITE (CALCIUM CARBONATE, 50-60%, CAS#471-34-1) FOR CRYSTALLINE SILICA AS QUARTZ, <1%. CAS# 14808-60-7, ACGIH TLV-0.1MG/M3 TWA, OSHA PEL-0.1 MG/M3 TWA. MAGNESIUM CARBONATE, CAS#546-93-0, 40-50%, ACGIH TLV-10MG/M3 TWA, OSHA PEL-15MG/M3 TWA TOTAL DUST, 5MG/M3 TWA, RESPIRABLE FRACTION. CALCIUM CARBONATE, CAS#471-34-1, 50-60%, ACGIH TLV-10 MG/M3 TWA, OSHA PEL-15MG/M3 TWA TOTAL DUST, 5MG/M3 TWA RESPIRABLE FRACTION.	MIXTURE	N/A N/A	5.5
TITANIUM DIOXIDE TITANIUM DIOXIDE, >93%, CAS#13463-67-7, ACGIH TLV-10MG/M3, TOTAL DUST 8 HR TWA, OSHA PEL-15MG/M3, TOTAL DUST, 8 HR TWA, AEL(ACCEPTABLE EXPOSURE LIMIT) OF 10MG/M3, TOTAL DUST 8 HR TWA, 5MG/M3 RESPIRABLE DUST 8 HR TWA. (AEL IS THE EXPOSURE LIMIT RECOMMENDED BY THE MANUFACTURER OF THIS CHEMICAL). AMORPHOUS SILICA, 3%, CAS#7631-86-9, ACGIH TLV-10MG/M3, TOTAL DUST 8 HR TWA OSHA PEL-80MG/M3 / % SiO2-8 HR TWA, AEL-3MG/M3, 8 HR TWA, RESPIRABLE DUST. AEL-6MG/M3, 8 HR TWA, TOTAL DUST. ALUMINUM HYDROXIDE, 2.5%, CAS#21645-51-2, NO EXPOSURE GUIDELINES HAVE BEEN ESTABLISHED FOR THIS CHEMICAL.	13463-67-7	N/A N/A	2
1,2 - PROPANEDIOL (PROPYLENE GLYCOL) AIHA WEEL IS 50 PPM TOTAL; 10MG/M3 AEROSOL ONLY. THERE IS NO OSHA PEL OR ACGIH TLV FOR PROPYLENE GLYCOL. AIHA = AMERICAN INDUSTRIAL HYGIENE ASSOCIATION. WEEL = WORKER ENVIRONMENTAL EXPOSURE LIMIT.	57-55-6	0.08 68F/20C	1

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.  
 # INDICATES CARCINOGENIC CHEMICAL. THIS MSDS MAY BE USED FOR OTHER COLORS AND FOR OTHER GRADES AND TEXTURES OF THIS PRODUCT.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 212F/100C - 370°F/188°C  
 VAPOR DENSITY: LIGHTER THAN AIR  
 COATING V.O.C.: 0.48 lb/gal  
 MATERIAL V.O.C.: 0.31 lb/gal  
 SOLUBILITY IN WATER: SOLUBLE.  
 APPEARANCE AND ODOR: HIGHLY THIXOTROPIC LIQUID, SLIGHT AMMONIACAL ODOR.

SPECIFIC GRAVITY (H2O=1): 1.87  
 EVAPORATION RATE: SLOWER THAN ETHER  
 COATING V.O.C.: 57 g/l  
 MATERIAL V.O.C.: 38 g/l

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: >205F/96C SETA FLASH CLOSED CUP.  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6% UPPER: 12.5%  
 EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG OR SPRAY, AS APPROPRIATE FOR SURROUNDING FIRE.

**SPECIAL FIREFIGHTING PROCEDURES**

DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS (PRESSURE-DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) TO PROTECT AGAINST THE HAZARDOUS EFFECTS OF COMBUSTION PRODUCTS AND OXYGEN DEFICIENCY.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

USE WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND TO COOL FIRE EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE RUPTURE OF CONTAINER. MATERIAL CAN SPLATTER ABOVE 212F/100C.

===== **SECTION V - REACTIVITY DATA** =====

**STABILITY:** STABLE

**CONDITIONS TO AVOID**

AVOID TEMPERATURES ABOVE 350F/177C, THE ONSET OF POLYMER DECOMPOSITION. THERMAL DECOMPOSITION IS DEPENDENT ON TIME AND TEMPERATURE.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

AVOID STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM HYPOCHLORITE OR CALCIUM HYPOCHLORITE.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

THERMAL DECOMPOSITION MAY YIELD ACRYLIC MONOMER, CARBON MONOXIDE AND CARBON DIOXIDE. UNIDENTIFIED ORGANIC COMPOUNDS IN FUMES AND SMOKE MAY BE FORMED DURING COMBUSTION.

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

===== **SECTION VI - HEALTH HAZARD DATA** =====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

VAPOR OR SPRAY MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SLIGHTLY IRRITATING TO THE SKIN. EYE CONTACT WITH VAPOR AND/OR SPRAY MIST MAY IRRITATE THE EYES. EYE CONTACT WITH LIQUID MAY RESULT IN SEVERE IRRITATION.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

NOT KNOWN.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

MAY CAUSE ABDOMINAL PAIN, NAUSEA AND VOMITING.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE: HEADACHE, NAUSEA, ABDOMINAL PAIN AND IRRITATION OF THE NOSE, THROAT AND LUNGS. SKIN AND EYE IRRITATION. CHRONIC: NOT ESTABLISHED. THE EFFECTS OF OVEREXPOSURE ARE BASED ON THE TOXICITY PROFILES FOR A NUMBER OF ACRYLIC EMULSIONS THAT ARE COMPOSITIONALLY SIMILAR TO THIS EMULSION.

TYPICAL DATA ARE:

ORAL LD50 - RAT: > 5000 MG/KG.

DERMAL LD50 - RABBIT: >5000 MG/KG.

SKIN IRRITATION - RABBIT: PRACTICALLY NON-IRRITATING.

EYE IRRITATION - RABBIT: INCONSEQUENTIAL IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN:** YES

**IARC MONOGRAPHS:** YES

**OSHA REGULATED:** YES

CONTAINS CRYSTALLINE SILICA. OVEREXPOSURE TO RESPIRABLE CRYSTALLINE SILICA DUST CAN CAUSE SILICOSIS, A FORM OF PROGRESSIVE PULMONARY FIBROSIS. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS EVALUATED IN VOLUME 42, MONOGRAPHS ON THE EVALUATION OF THE CARCINOGENICITY RISK OF CHEMICALS TO HUMANS, SILICA AND SOME SILICATES (1987), THAT THERE IS "SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA TO EXPERIMENTAL ANIMALS" AND "LIMITED EVIDENCE" WITH RESPECT TO HUMANS AND HAS BEEN CLASSIFIED AS A GROUP 2A CARCINOGEN BY THE IARC. "LIMITED" MEANS A POSITIVE ASSOCIATION HAS BEEN OBSERVED, BUT CHANCE, BIAS OR CONFOUNDING FACTORS COULD NOT BE RULED OUT. OTHER HUMAN HEALTH STUDIES HAVE DEMONSTRATED A NEGATIVE ASSOCIATION FOR CANCER. CRYSTALLINE SILICA IS ALSO LISTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP) AS A SUBSTANCE REASONABLY ANTICIPATED TO BE A CARCINOGEN AS A RESPIRABLE DUST. CONSIDERABLE CONTROVERSY EXISTS CONCERNING THE IARC AND NTP CLASSIFICATION.

REMAINING INGREDIENTS ARE AT OR LESS THAN *de minimis* CONCENTRATIONS OR ARE NOT CONSIDERED TO BE CARCINOGENS BY THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER OR BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

PERSONS WITH PRE-EXISTING EYE OR PULMONARY DISEASE MAY BE SUSCEPTIBLE TO AGGRAVATION FROM EXPOSURE.

**EMERGENCY AND FIRST AID PROCEDURES**

EYES: IMMEDIATELY FLUSH WITH LOTS OF WATER FOR AT LEAST 15 MINUTES. IF REDNESS, ITCHING, OR A BURNING SENSATION DEVELOPS SEE A PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING/SHOES & WIPE OFF EXCESS FROM SKIN. WASH WITH PLENTY OF SOAP AND WATER. IF REDNESS, ITCHING OR A BURNING SENSATION DEVELOPS, GET

MEDICAL ATTENTION. INHALATION: REMOVE PATIENT TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN, ADMINISTERED BY A QUALIFIED INDIVIDUAL ONLY. CALL A PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

WEAR SKIN, EYE & RESPIRATORY PROTECTION DURING CLEAN-UP. EVACUATE AREA OF ALL NON-ESSENTIAL PERSONNEL. SHUT OFF OR REMOVE ALL IGNITION SOURCES. VENTILATE SPILL AREA. DIKE, AND CONTAIN AND/OR ABSORB WITH INERT MATERIAL (SAND, EARTH OR OTHER SUITABLE NON-COMBUSTIBLE MATERIAL) TO PREVENT ENTRY INTO STORMDRAINS, SEWERS AND OTHER UNAUTHORIZED TREATMENT/DRAINAGE SYSTEMS AND NATURAL WATERWAYS. SCOOP UP AND PLACE IN APPROVED CONTAINERS FOR PROPER DISPOSAL. COVER WITH LID. IF SPILL OCCURS NEAR AIR INLETS OR INSIDE, TURN OFF HEATING OR AIR-CONDITIONING EQUIPMENT TO PREVENT CONTAMINATING BUILDING.

**WASTE DISPOSAL METHOD**

DISPOSE OF UNUSED PRODUCT OR CONTAMINATED PRODUCT AND MATERIALS USED IN CLEANING UP SPILLS OR LEAKS IN A MANNER APPROVED FOR THIS MATERIAL. CONSULT APPROPRIATE FEDERAL, STATE AND LOCAL REGULATORY AGENCIES TO ASCERTAIN PROPER DISPOSAL PROCEDURES. INCINERATION IS ACCEPTABLE AND THE PREFERRED METHOD OF DISPOSAL, HOWEVER; NITROGEN OXIDE EMISSIONS CONTROLS MAY BE REQUIRED TO MEET SPECIFICATIONS. CHEMICAL AND BIOLOGICAL DEGRADATION IS POSSIBLE. A SUITABLE INDUSTRIAL OR MUNICIPAL WASTE TREATMENT SYSTEM CAN BE USED DEPENDING ON THE QUALITY AND QUANTITY OF WASTE TO BE TREATED, THE TREATMENT PLANT CAPABILITY, AND DISCHARGE WATER QUALITY STANDARDS. DISPOSE OF IN AN APPROVED LANDFILL IF ALLOWED LOCALLY. EMPTY CONTAINERS WILL RETAIN PRODUCT RESIDUE AND VAPORS AND ARE SUBJECT TO PROPER WASTE DISPOSAL, AS ABOVE.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP FROM FREEZING. KEEP CONTAINER COOL AND DRY. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION. KEEP PRODUCT CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. AVOID SUBJECTING THIS PRODUCT TO EXTREME TEMPERATURE VARIATIONS.

**OTHER PRECAUTIONS**

CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, WILL RETAIN PRODUCT RESIDUE & VAPORS. ALWAYS OBEY HAZARD WARNINGS AND HANDLE EMPTY CONTAINERS AS IF THEY WERE FULL. DO NOT USE PRESSURE TO EMPTY CONTAINER. DO NOT PUNCTURE, CUT, GRIND, WELD, BRAZE, SOLDER OR DRILL ON OR NEAR THIS CONTAINER OR OTHERWISE EXPOSE SUCH CONTAINER TO HEAT, FLAME, SPARKS, STATIC ELECTRICAL CHARGES, ELECTRICITY OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND/OR EMIT TOXIC VAPORS RESULTING IN INJURY OR DEATH. CLOSED CONTAINERS MAY EXPLODE DUE TO PRESSURE BUILD-UP IF EXPOSED TO EXTREME HEAT. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR OR SPRAY MIST. USE ONLY IN A WELL VENTILATED AREA. KEEP OUT OF THE REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

WEAR A NIOSH APPROVED RESPIRATOR APPROPRIATE FOR THE VAPOR OR MIST CONCENTRATION AT THE POINT OF USE. APPROPRIATE RESPIRATORS MAY BE A FULL FACEPIECE OR A HALF MASK AIR-PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPORS/MISTS, A SELF-CONTAINED BREATHING APPARATUS IN THE PRESSURE DEMAND MODE, OR A SUPPLIED AIR RESPIRATOR. REFER TO OSHA STANDARD 29 CFR 1910.134 FOR ADDITIONAL INFORMATION.

**VENTILATION**

IF CURRENT VENTILATION PRACTICES DURING MIXING AND APPLICATION OPERATIONS ARE NOT ADEQUATE TO MINIMIZE EXPOSURE, USE LOCAL EXHAUST VENTILATION CAPABLE OF MAINTAINING EMISSIONS AT THE POINT OF USE BELOW THE PEL OR TLV OR OTHER EXPOSURE GUIDELINES, AS APPROPRIATE. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS. MECHANICAL EXHAUST VENTILATION, WITH VOLUME AND PATTERN CAPABLE OF MAINTAINING A FRESH AIR SUPPLY, MAY BE NECESSARY IN CONFINED SPACES. REFER TO OSHA STANDARD 29 CFR 1910.94 AND/OR ACGIH INDUSTRIAL VENTILATION FOR GUIDANCE ABOUT ADEQUATE VENTILATION. TURN OFF HEATING AND/OR AIR CONDITIONING EQUIPMENT TO PREVENT CONTAMINATING BUILDING.

**PROTECTIVE GLOVES**

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION. NOTE THAT PVA DEGRADES IN WATER.

**EYE PROTECTION**

USE CHEMICAL GOGGLES. WEAR A FACE SHIELD IF SPLASHING MAY OCCUR OR DURING SPRAY OPERATIONS, UNLESS A FULL FACE PIECE RESPIRATOR IS USED. DO NOT WEAR CONTACT LENSES AS THEY MAY CONTRIBUTE TO THE SEVERITY OF INJURY TO THE EYE FROM EXPOSURE TO LIQUID AND/OR VAPORS AND SPRAY MIST.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

LONG SLEEVED SHIRT, TROUSERS, SAFETY SHOES AND GLOVES. AN EYEWASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE & READY FOR USE. IMPERVIOUS CLOTHING SHOULD BE WORN AS NEEDED. PROTECTIVE CLOTHING SHOULD BE SELECTED AND USED IN ACCORDANCE WITH "GUIDELINES FOR THE SELECTION OF CHEMICAL PROTECTIVE CLOTHING" PUBLISHED BY ACGIH. (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS).

**WORK/HYGIENIC PRACTICES**

WASH AT THE END OF EACH WORKSHIFT AND BEFORE EATING, SMOKING OR USING THE TOILET. PROMPTLY REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE WEARING. DISCARD CONTAMINATED LEATHER ARTICLES. EXAMINE PROTECTIVE GLOVES AND CLOTHING BEFORE USE. DISCARD UPON FINDING EVIDENCE OF HOLES CRACKS OR LEAKS.

**ADDITIONAL REGULATORY INFORMATION**

STATUS OF SUBSTANCE LISTS: THE CONCENTRATIONS SHOWN IN SECTION II AND/OR IN THIS SECTION, ARE MAXIMUM FOR CEILING LEVELS (WEIGHT %) TO BE USED FOR CALCULATIONS FOR REGULATIONS. FEDERAL EPA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT OF 1980 (CERCLA) REQUIRES NOTIFICATION OF THE NATIONAL RESPONSE CENTER OF RELEASE OF QUANTITIES OF HAZARDOUS SUBSTANCES EQUAL TO OR GREATER THAN THEREPORTABLE QUANTITIES (RQs) IN 40 CFR 302.4.

COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL THAT COULD REQUIRE REPORTING UNDER THE STATUTE ARE: NONE KNOWN.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III REQUIRES EMERGENCY PLANNING BASED ON THRESHOLD PLANNING QUANTITIES ( TPQs) AND RELEASE REPORTING BASED ON REPORTABLE QUANTITIES (RQs) IN 40 CFR 355 (USED FOR SARA 302, 304, 311 AND 312).

COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL THAT COULD REQUIRE REPORTING UNDER THE STATUTE ARE: NONE KNOWN.

REQUIRES SUBMISSION OF ANNUAL REPORTS OF RELEASE OF TOXIC CHEMICALS THAT APPEAR IN 40 CFR 372 (FOR SARA 313). THIS INFORMATION MUST BE INCLUDED IN ALL MSDSs THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL THAT COULD REQUIRE REPORTING UNDER THE STATUTE ARE: NONE KNOWN

STATE RIGHT TO KNOW: CALIFORNIA PROPOSITION 65: SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE), KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

IN ADDITION TO THE ABOVE NAMED CHEMICALS, IF ANY, THIS PRODUCT MAY CONTAIN TRACE AMOUNTS OF SOME CHEMICALS CONSIDERED BY THE STATE OF CALIFORNIA TO BE CARCINOGENS OR REPRODUCTIVE TOXICANTS.

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS:

THE COMPONENTS OF THIS PRODUCT ARE LISTED OR ARE EXCLUDED FROM LISTING ON THE U.S. TOXIC SUBSTANCES CONTROL ACT (TSCA) CHEMICAL SUBSTANCE INVENTORY.

THE REMAINING PERCENTAGE OF UNSPECIFIED INGREDIENTS ARE NOT CONTAINED IN ABOVE *de minimis* CONCENTRATIONS AND/OR ARE BELIEVED TO BE NON-HAZARDOUS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), AND MAY CONSIST OF PIGMENTS, FILLERS, DEFOAMERS, WETTING AGENTS, ANTI-BACTERIAL AGENTS, RESINS, DRYERS, WATER AND/OR SOLVENTS IN VARYING CONCENTRATIONS. THIS PRODUCT IS BELIEVED TO NOTCONTAIN MERCURY COMPOUNDS OR FORMALDEHYDE.

**===== SECTION IX - DISCLAIMER =====**

THE INFORMATION CONTAINED HEREIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND. USERS SHOULD CONSIDER THESE DATA ONLY AS A SUPPLEMENT TO OTHER INFORMATION GATHERED BY THEM & DETERMINE THE SUITABILITY & COMPLETENESS OF INFORMATION FROM ALL SOURCES TO ASSURE PROPER USE & DISPOSAL OF THESE MATERIALS & THE SAFETY & HEALTH OF EMPLOYEES & CUSTOMERS.