

FINE TEXTURE

“Tape & Float Stucco”

Technical Data & Application Instructions

PRODUCT DESCRIPTION

CARRARA FINE TEXTURE is a 100% acrylic polymer mastic combined with fine white mineral aggregate, antibacterial and anti-mildew agents, hydrophobic and other agents, along with color stable acrylic colorants that results in a uniform, weatherproof textured stucco finish.

SURFACE PREPARATION

Apply an even coat of the specified color coordinated **COLORFLEX** base coat by brush, paint roller or spray equipment. Allow to dry at least four (4) hours or until completely dry. The Fine Texture finish should be pre-mixed for 1 to 1-1/2 minutes with a Goldblatt Jiffler mixer powered by a half-inch drill, 400-500 RPM, just prior to application.

APPLICATION

Fine Texture may be applied by trowel, Carrara Texture Sprayer or hopper gun. When using a hopper or Texture Sprayer, the mastic may be reduced with water, sparingly, no more than one pint per five-gallon pail to create a greater or smoother flow. Hand held hoppers are adequate for small areas; industrial texture “pressure pot” delivery equipment is recommended for larger areas (2,000 sq. ft. or more). Optimum coverage for Fine Texture is 150 to 175 sq. ft. per pail. Greater coverage rates will result in background show through, mottling and inconsistent appearance. Carrara should not be applied greater than 3- mm (1.8”) thick in a single coat. If applied greater than 3 mm (1/8”), cracks or blisters may result in localized delamination. Regulating air pressure beforehand will achieve different textures. Higher air pressures result in a finer texture; a lower air pressure results in larger and heavier texture.

CLEAN-UP

Clean tools with water before material dries.

LIMITATIONS & PRECAUTIONS

FINE TEXTURE will freeze and become unusable at temperatures below 32° F (0° C). Do not ship or store without protection from freezing temperatures. Do not apply at ambient temperatures below 50° F (10° C) or surface temperatures below 40° F (4.4° C) or if rain is expected. Cool temperatures and high humidity will retard drying time. Close container after each use.

Avoid contact with eyes and skin. For additional information on safety requirements, refer to OSHA guidelines and **FINE TEXTURE** Material Data Safety Sheet.



Voice (512) 267-5888 Fax (512) 261-4441

www.globalcoatings.com