

MEDIUM TEXTURE

--Tape & Float Stucco--

Technical Data & Application Instructions

GLOBAL COATINGS
April, 2009

PRODUCT DESCRIPTION

CARRARA MEDIUM TEXTURE is an acrylic polymer mastic combined with mineral aggregate, antibacterial and anti-mildew agents, hydrophobic and other agents, along with color stable acrylic colorants that results in a uniform, weatherproof worm-textured stucco finish.

SURFACE PREPARATION

Apply an even coat of the specified color coordinated **COLORFLEX** base coat by brush, paint roller or spray equipment. Allow to dry at least four (4) hours or until completely dry. The Medium Texture finish should be pre-mixed for 1 to 1-1/2 minutes with a Goldblatt Jiffler mixer powered by a half-inch drill, 400-500 RPM, just prior to application.

APPLICATION

Medium Texture is applied by trowel & plastic or steel float. The mastic may be reduced with water, sparingly, no more than one pint per five-gallon pail to create a greater or smoother flow. Estimated coverage for Medium Texture is 100 to 115 sq. ft. per pail. Greater coverage rates will result in background show through, mottling and inconsistent appearance. Carrara should not be applied greater than 3- mm (1.8") thick in a single coat. If applied greater than 3 mm (1/8"), cracks or blisters may result in localized delamination.

CLEAN-UP

Clean tools with water before material dries.

LIMITATIONS & PRECAUTIONS

MEDIUM TEXTURE will freeze and become unusable at temperatures below 32° F (0° C). Do not ship or store without protection from freezing temperatures. Do not apply at ambient temperatures below 50° F (10° C) or surface temperatures below 40° F (4.4° C) or if rain is expected. Cool temperatures and high humidity will retard drying time. Close container after each use.

Avoid contact with eyes and skin. For additional information on safety requirements, refer to OSHA guidelines and **MEDIUM TEXTURE** Material Data Safety Sheet.



Voice (888) 947-5870 Fax (512) 261-4441

www.carrara-stucco.com

Our data and suggestions are based on information from laboratory and field testing which we believe to be reliable. Because methods of application vary with each situation, we cannot guarantee or accept any liability resulting from the use of our products. Avoid contact with eyes and skin. For additional information on **ACRACREAM** safety requirements, refer to OSHA guidelines and Material Data Safety Sheet.