

SONORA SAND TEXTURE

Very Fine Sand Texture

Technical Data & Application Instructions

PRODUCT DESCRIPTION

CARRARA SONORA SAND TEXTURE is an acrylic polymer mastic combined with fine quartz aggregate, antibacterial and anti-mildew agents, hydrophobic and other agents, along with color stable acrylic colorants that results in a uniform, weatherproof textured stucco finish.

SURFACE PREPARATION

Apply an even coat of the specified color coordinated **COLORFLEX** base coat by brush, paint roller or spray equipment. Allow to dry at least four (4) hours or until completely dry. The Sonora Sand Texture finish should be pre-mixed for 1 to 1-1/2 minutes with a Goldblatt Jiffler mixer powered by a half-inch drill, 400-500 RPM, just prior to application.

APPLICATION

Sonora Sand Texture is typically applied by trowel and plastic float. The Carrara Texture may be reduced with water, sparingly, no more than one pint per five-gallon pail to create a greater or smoother flow.

Estimated coverage for Sonora Sand Texture is 150 to 200 sq. ft. per pail (smooth flat application); 50 – 100 sq. ft. for Skip Trowel (varies by application). Greater coverage rates will result in background show through, mottling and inconsistent appearance. Carrara should not be applied greater than 3- mm (1.8") thick in a single coat. If applied greater than 3 mm (1/8"), cracks or blisters may result in localized delamination.

Sonora Sand Texture is ideal for skip trowel or lace texture applications. Trowel a base-coat and allow to dry. Follow with the finish texture technique of choice.

CLEAN-UP

Clean tools with water before material dries.

LIMITATIONS & PRECAUTIONS

SONORA SAND TEXTURE will freeze and become unusable at temperatures below 32° F (0° C). Do not ship or store without protection from freezing temperatures. Do not apply at ambient temperatures below 50° F (10° C) or surface temperatures below 40° F (4.4° C) or if rain is expected. Cool temperatures and high humidity will retard drying time. Close container after each use.

Avoid contact with eyes and skin. For additional information on safety requirements, refer to OSHA guidelines and **SONORA SAND TEXTURE** Material Data Safety Sheet.



Voice (888) 947-5870 Fax (512) 261-4441

www.carrara-stucco.com